



## Joyroom kabel przewód USB Typ C - USB Typ C PD 60W 1,2m biały (S-1230N9)

Indeks: **145323** Producent: **Joyroom** Kod producenta: **6941237130709**

**Cena: 22.32 zł**

### Opis

## Joyroom kabel przewód USB Typ C - USB Typ C PD 60W 1,2m biały (S-1230N9)

Producent: Joyroom

- **Głębokość opakowania towaru w cm:** 9,5
- **Wysokość opakowania towaru w cm:** 2,5
- **Szerokość opakowania towaru w cm:** 15,5
- **EAN:** 6941237130709
- **Kod producenta:** S-1230N9
- **Kolor wiodący:** Biały
- **Typ opakowania:** Pudełko
- **Długość przewodu (m):** 1,2
- **Funkcje przewodu:** Dane, Ładowanie
- **Maksymalne obciążenie (W):** 60
- **Standard szybkiego ładowania:** USB Power Delivery
- **Standard USB:** USB 2.0 High Speed (480 Mbps)
- **Typ złącza:** USB Typ C (męski)

### Parametry

<b>Producent</b>	Joyroom
<b>Kod producenta</b>	6941237130709
<b>EAN</b>	6941237130709
<b>Kolor</b>	biały
<b>Długość przewodu</b>	1.2
<b>Złącza</b>	USB typ C - USB typ C
<b>Stan</b>	Nowy

### Zdjęcia



**JOYROOM**  
Make things be better

N9

**Antiflaming Antifreeze**  
-60°C-350°C  
keep good elasticity at 40-200°C

**Food Grade**  
Soft cable made of liquid silicone, strong anti-fouling, never fading and washable.

**Kevlar**  
30,000 times of violent bending test, 6 times endurance than the common cables.

**PD Liquid Silicone data cable**

**1.8M**  
Quick Charging  
**2.4A/3A**

**PD Liquid Silicone data cable**

**PD Liquid Silicone data cable**

**Kevlar** was the earliest ideal aviation material and now it's mainly used to make bulletproof vests, cables, high-pressure hoses, transportation belts, etc. It is supported during high-pressure research, rocket engine cases, radar radomes; it also can replace the steel bars in high-rise buildings and etc.

The same liquid silicone cable with the phone case, food-grade environmental protection silicone material.

Soft cable made of liquid silicone, strong anti-fouling, never fading and washable.

**Silicone cable + heat insulation** (Improved/antifreezing premium material, -60-200°C good elasticity, anti-deformation. Stable at -150°C - 250°C).

**Reinforced SE design**, built-in Kevlar, 30000 times bending test, 6 times endurance than the common cables.

**PD fast charging**, thickened cable core, stable charging and current with premium copper wire etc.

Type-C to Lightning	Type-C to Type-C
Supports up to 12W, 2.4A, 20W Max. Fast Charging	Supports up to 12W, 2.4A, 20W Max. Fast Charging