



Płyta Gigabyte H610M S2H DDR4 (rev. 1.0)/H610/DDR4/SATA3/M.2/USB3.0/PCIe4.0/s.1700/mATX

Indeks: 148499 Producent: GIGABYTE Kod producenta: H610M S2H DDR4

Cena: 401.67 zł

Opis

Płyta Gigabyte H610M S2H DDR4 (rev. 1.0)/H610/DDR4/SATA3/M.2/USB3.0/PCIe4.0/s.1700/mATX

CPU LGA1700 socket: Support for 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors* L3 cache varies with CPU * Please refer to "CPU Support List" for more information. Chipset Intel® H610 Express Chipset Memory Support for DDR4 3200/3000/2933/2666/2400/2133 MHz memory modules 2 x DDR4 DIMM sockets supporting up to 64 GB (32 GB single DIMM capacity) of system memory Dual channel memory architecture Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode) Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules Support for Extreme Memory Profile (XMP) memory modules (Please refer "Memory Support List" for more information.) Onboard Graphics Integrated Graphics Processor-Intel® HD Graphics support:1 x D-Sub port, supporting a maximum resolution of 1920x1200@60 Hz 1 x DVI-D port, supporting a maximum resolution of 1920x1200@60 Hz* The DVI-D port does not support D-Sub connection by adapter. 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz* Support for HDMI 2.1 version and HDCP 2.3.** Support native HDMI 2.1 TMDS compatible ports 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz* Support for DisplayPort 1.2 version and HDCP 2.3 (Graphics specifications may vary depending on CPU support.) Audio Realtek® Audio CODEC High Definition Audio 2/4/5.1/7.1-channel* To configure 7.1-channel audio, you need to open the audio software and select Device advanced settings > Playback Device to change the default setting first. Please visit GIGABYTE's website for details on configuring the audio software. LAN Intel® GbE LAN chip (1 Gbps/100 Mbps) Expansion Slots 1 x PCI Express x16 slot, running at x16* For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot.(The PCI Express x16 slot conforms to PCI Express 4.0 standard.) 1 x PCI Express x1 slot(The PCI Express x1 slot conforms to PCI Express 3.0 standard.) Storage Interface Chipset:1 x M.2 connector (Socket 3, M key, type 2260/2280 PCIe 3.0 x4/x2 SSD support) 4 x SATA 6Gb/s connectors USB Chipset:4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports available through the internal USB header) 4 x USB 2.0/1.1 ports on the back panel Chipset+USB 2.0 Hub:4 x USB 2.0/1.1 ports available through the internal USB headers Internal I/O Connectors 1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 1 x M.2 Socket 3 connector 4 x SATA 6Gb/s connectors 1 x CPU fan header 2 x system fan headers 1 x RGB LED strip header 1 x front panel header 1 x front panel audio header 1 x USB 3.2 Gen 1 header 2 x USB 2.0/1.1 headers 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only) 1 x serial port header 1 x Clear CMOS jumper Back Panel Connectors 1 x PS/2 keyboard port 1 x PS/2 mouse port 1 x D-Sub port 1 x DVI-D port 1 x DisplayPort 1 x HDMI 2.0 port 2 x USB 3.2 Gen 1 ports 4 x USB 2.0/1.1 ports 1 x RJ-45 port 3 x audio jacks I/O Controller iTE® I/O Controller Chip H/W Monitoring Voltage detection Temperature detection Fan speed detection Overheating warning Fan fail warning Fan speed control* Whether the fan speed control function is supported will depend on the cooler you install. BIOS 1 x 256 Mbit flash Use of licensed AMI UEFI BIOS PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0 Unique Features Support for APP Center* Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.@BIOSAmbient LEDEasyTuneFast BootGame BoostON/OFF ChargeSmart BackupSystem Information Viewer Support for Q-Flash Support for Xpress Install Bundled Software Norton® Internet Security (OEM version) LAN bandwidth management software Operating System Support for Windows 11 64-bit Support for Windows 10 64-bit Form Factor Micro ATX Form Factor; 23.0cm x 21.5cm

Parametry

Model	H610M S2H DDR4
Producent	Gigabyte
EAN	4719331830427
Chipset	Intel
Kod producenta	H610M S2H DDR4
Obsługiwane procesory	Intel
Standard płyty	Micro ATX
Typ obsługiwanej pamięci	DDR4

Maksymalna ilość pamięci RAM	64
Liczba slotów pamięci RAM	2
Szerokość	230
Stan	Nowy

Zdjęcia



H610M S2H DDR4

GIGABYTE



Rodzaj pamięci DDR4	Maksymalna pamięć 64GB	Procesor Gniazdo procesora: LGA1700 Rodzina procesora: Bez procesora	Format płyty micro ATX	Złącza zewnętrzne <ul style="list-style-type: none"> 1x PS/2 Myszka 1x PS/2 Klawiatura 1x D-Sub 1x DisplayPort 1x DVI-D 1x HDMI 1x Line In 1x Line Out 1x MIC 1x RJ-45 4x USB 2.0 2x USB 3.0
Ilość złącz SATA 4		RAID	Interfejs sieciowy 1x 10/100/1000 Mb/s	