



Router Asus ROG Rapture GT-AX11000 PRO Wi-Fi AX11000 1xWAN/LAN 10Gb/s 1xWAN 2,5Gb/s 4x LAN 1Gb/s

Indeks: **207854** Producent: **ASUS** Kod producenta: **GT-AX11000 PRO**

Cena: 2,364.87 zł

Opis

Router Asus ROG Rapture GT-AX11000 PRO Wi-Fi AX11000 1xWAN/LAN 10Gb/s 1xWAN 2,5Gb/s 4x LAN 1Gb/s

Model Name GT-AX11000 PRO Network Standard IEEE 802.11ax IPv4 IPv6 Product Segment AX11000 ultimate AX performance AX technology Yes Data Rate 2.4GHz AX: 4x4 (Tx/Rx) 1024 QAM 20/40MHz, up to 1148Mbps 5G-1Hz AX: 4x4 (Tx/Rx) 1024 QAM 20/40/80/160MHz, up to 4804Mbps 5G-2Hz AX: 4x4 (Tx/Rx) 1024 QAM 20/40/80/160MHz, up to 4804Mbps Antenna External antenna x 8 (non-detachable) Transmit/Receive 2.4 GHz 4 x 4 5 GHz-1 4 x 4 5 GHz-2 4 x 4 Processor 2.0GHz quad-core processor Memory 256MB NAND flash and 1GB DDR4 RAM Boosts speed OFDMA (Orthogonal Frequency Division Multiple Access) Beamforming: standard-based and universal 1024-QAM high data rate 20/40/80/160 MHz bandwidth * The 160MHz bandwidth may be unavailable in the 5GHz band in some regions / countries due to regulatory restrictions. Operating Frequency Tri-band Wi-Fi: 2.4 GHz / 5 GHz-1 / 5 GHz-2 Ports 1 x 2.5 Gigabit WAN Port 1 x 10 Gigabit WAN/LAN Port 4 x Gigabit LAN Ports 1 x USB 3.2 Gen 1 Port 1 x USB 2.0 Port Button WPS Button, LED Button, Reset Button, Power Switch LED Indicator Power x 1 2.4G x 1 5GHz-1 x 1 5GHz-2 x 1 WPS x 1 10GE x 1 LAN x 1 WAN x 1 Power Supply AC Input : 110V~240V(50~60Hz) DC Output : 19 V with max. 3.42 A ; 19.5 V with max. 3.33 A Package content GT-AX11000 Pro WiFi Gaming Router RJ-45 Cable Power Adapter Quick Start Guide Warranty Card Product Weight (g) 2180g AiMesh AiMesh Primary AiMesh router AiMesh node Router APP ASUS Router APP Game Game Boost/acceleration Game Radar WTFast UU boost ROG_First OpenNAT (Game Profile) Alexa Support Alexa skill AiProtection AiProtection Pro Router Security Assessment Malicious site blocking Two-Way IPS Infected Device Prevention and Blocking Parental Control Parental Control Parental Control Customized Internet schedule Maximum Parental Control profile : 64 Maximum Parental Control content filter rule : 64 Traffic Control Adaptive QoS Bandwidth Monitor Bandwidth limiter Maximum Bandwidth limiter rule : 32 Traditional QoS Traffic Monitor Real-time traffic monitor Wired Traffic Monitor Wireless Traffic Monitor Traffic Analyzer Traffic analysis period : Daily, Weekly, Monthly Website history Wireless IPv6 MU-MIMO WiFi Encryption : WPA3 Personal, WPA2 Personal, WPA Personal, WPA Enterprise, WPA2 Enterprise, Open System UTF-8 SSID Guest Network Maximum Guest Network rule : 2.4 GHz x 3, 5 GHz-1 x 3, 5 GHz-2 x 3 Guest Network Connection time limit Guest Network Encryption : Open system, WPA/WPA2-Personal/WPA3-Personal WPS Wi-Fi MAC address filter Maximum MAC filters : 64 Wireless scheduler Airtime fairness RADIUS Server Universal beamforming WAN Explicit beamforming Internet connection Type : Automatic IP, Static IP, PPPoE, PPTP, L2TP Dual WAN WAN Aggregation 3G/4G LTE dongle Android tethering Port forwarding Maximum port forwarding rule : 64 Port triggering Maximum port triggering rule : 32 DMZ DDNS NAT Passthrough : PPTP, L2TP, IPSec, RTSP, H.323, SIP Passthrough, PPPoE relay Let's Encrypt LAN DHCP Server IGMP snooping IPTV LAN Link Aggregation Manually assign IP address Maximum manually assign IP address rule : 128 VPN VPN Client L2TP VPN Client OVPN VPN Client PPTP VPN Server IPSec VPN Server OVPN VPN Server PPTP VPN Fusion USB application File System : HFS+, NTFS, vFAT, ext2, ext3, ext4 HDD hibernation Safely Remove disk AiCloud Download master AiDisk Media Server Time Machine Samba Server FTP Server Shared Folder privileges Administration Operating mode : Router(AiMesh router), AiMesh node, Access point, Repeater, Media bridge Operating system : ASUSWRT Free OS upgrade Firewall Maximum Firewall keyword filter : 64 Maximum Firewall

network service filter : 32 Maximum Firewall URL filter : 64 Wake on LAN (WOL) SSH Configuration backup and restore
Diagnosis tools Feedback system System log Actual data throughput and WiFi coverage will vary from network conditions and environmental factors, including the volume of network traffic, building material and construction, and network overhead, result in lower actual data throughput and wireless coverage. Quoted network speeds and bandwidth based on current IEEE 802.11ac & 802.11ax specifications. Actual performance may be affected by network and service provider factors, interface type, and other conditions. Connected devices must be same standard for best results. WPA/WPA2 enterprise is only available on single router, is not available under AiMesh mode. Products certified by the Federal Communications Commission and Industry Canada will be distributed in the United States and Canada. Please visit the ASUS USA and ASUS Canada websites for information about locally available products. All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets. Specifications and features vary by model, and all images are illustrative. Please refer to specification pages for full details. PCB color and bundled software versions are subject to change without notice. Brand and product names mentioned are trademarks of their respective companies. Unless otherwise stated, all performance claims are based on theoretical performance. Actual figures may vary in real-world situations. The actual transfer speed of USB 3.0, 3.1, 3.2, and/or Type-C will vary depending on many factors including the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment.

Parametry

Producent	Asus
EAN	4711081264361
Kod producenta	90IG0720-MU2A00
Model	90IG0720-MU2A00
Tryb pracy	Router
Standard pracy bezprzewodowej	802.11a, 802.11ac (Wi-Fi 5), 802.11ax (Wi-Fi 6), 802.11b, 802.11g, 802.11n (Wi-Fi 4)
Pasma	2,4 GHz, 5 GHz
Wbudowany modem	brak modemu
Liczba portów LAN (RJ-45)	5
Standard pracy portów LAN	10/100/1000 Mbps
Szerokość produktu	355
Wysokość produktu	193
Głębokość produktu	355
Stan	Nowy

Zdjęcia

