



Switch D-Link DGS-1510-28X (24x 10/100/1000Mbps)

Indeks: 28999 Producent: D-Link Kod producenta: DGS-1510-28X

Cena: **1,797.04 zł**

Opis

DGS-1510-28X Switch 24xGb+4xSFP

Producent: D-Link

Właściwości

- Opis
- Klasa przełącznika **SMART**
- Zastosowanie (switche) **Średnie i duże firmy (powyżej 16 portów)**
- Warstwa przełączania (switche) **L2**
- Architektura sieci (switche) **GigabitEthernet**
- Liczba portów 10/100/1000 Mbps **24**
- Liczba portów SFP+ **4**
- Tryb przekazywania **Store-and-forward**
- Przepustowość (switche Gbps) **128**
- Prędkość przekazywania (Mpps) **95.24**
- Bufor pamięci (switche) **1.5**
- Rozmiar tablicy adresów MAC **16000**
- Możliwość łączenia w stos **Tak**
- VLAN - **802.1Q Tagged VLAN- 4K VLAN Groups- Configurable VID: 0~4094- GVRP- Asymmetric VLAN- Auto Voice VLAN- Auto Surveillance VLAN 2.02- MAC-based VLAN- Protocol-based VLAN**
- Obsługiwane protokoły i standardy - **IEEE 802.3- IEEE 802.3ab- IEEE 802.3ae- IEEE 802.3u- IEEE 802.3x**
- QoS - **CoS based on 802.1p priority VLAN MAC address Ether type IP address DSCP Protocol type TCP/UDP port number DSCP of IPv6 Traffic Class IPv6 flow label- 802.1p Quality of Service- Queue Handling Strict Priority Queue (SPQ) Weighted Round Robin (WRR) Deficit Round Robin (DRR) SPQ + WRR- 8 queues per port- Bandwidth Control Port-based (Ingress/Egress, min. granularity for 10/100/1000 BASE-T ports is 64 Kb/s)**
- Bezpieczeństwo - **Port Security Supports up to 128 MAC addresses per port- Broadcast/Multicast/Unicast Storm Control- Dynamic ARP Inspection- D-Link Safeguard Engine- DHCP Server Screening- ARP Spoofing Prevention Max. 64 entries- SSH Supports v2 Supports IPv4/IPv6- BPDU Attack Protection- DoS Attack Prevention- SSL Supports v1/v2/v3 Supports IPv4/IPv6- Traffic Segmentation- IP-MAC-Port Binding DHCP snooping IP Source Guard Dynamic ARP Inspection IPv6 DHCP Guard IPv6 RA Guard IPv6 Snooping IPv6 Source Guard IPv6 ND Inspection**

- Zarządzanie, monitorowanie, konfiguracja - **Command Line Interface (CLI)- Telnet Server- TFTP Client- IPv6 Neighbor Discovery- Configurable MDI/MDIX- SNMP**; Supports v1, v2c, v3- **SNMP Trap- System Log**; Max. 10,000 log entries- **Debug command- Dual images- Surveillance mode2- DHCP Client- D-Link Network Assistant support- SNTP- ICMPv6- IPv4/v6 Dual Stack- DHCP Auto Configuration- RMON v1- LLDP, LLDP-MED- DHCP relay- Web-based GUI- TFTP Client- NTP- Telnet client (supports CLI only)**
- Funkcje L2 - **MAC Address Table: Up to 16,384- Flow Control**; 802.3x **Flow Control**; **HOL Blocking Prevention- Jumbo Frame up to 9,216 Bytes- IGMP Snooping**; **IGMP v1/v2 Snooping**; **IGMP v3 awareness**; Supports 512 **IGMP groups**; Supports 128 **static multicast addresses**; **IGMP per VLAN**; Supports **IGMP Snooping Querier**; **Host-based IGMP Snooping Fast Leave- MLD Snooping**; Supports **MLD v1/v2 awareness**; Supports 512 **groups**; Supports 128 **Static Multicast Addresses**; **Per VLAN MLD Snooping**; **Host-based MLD Fast Leave**; **MLD Snooping Querier- Spanning Tree Protocol**; **802.1D STP**; **802.1w RSTP**; **802.1s MSTP- Loopback Detection v4.072- 802.3ad Link Aggregation**; Max. 32 **groups per device/8 ports per group- Port Mirroring**; Support 4 **mirroring groups**; **One-to-One, Many-to-One**; Supports **Mirroring for Tx/Rx/Both- Multicast Filtering**; **Forwards all unregistered groups**; **Filters all unregistered groups- Ethernet Ring Protection Switching (ERPS)**
- Typ obudowy **Rack (Switch/UPS)**
- Pobór mocy **22.3**
- Wymiary **440 x 210 x 44 mm**
- Waga **2**
- Pozostałe parametry **Certyfikaty:- CE- FCC- C-Tick- VCCI- BSMI- CCC**

Parametry

EAN	790069406058
Kod producenta	DGS-1510-28X
Liczba portów	28
Stan	Nowy
Producent	D-Link
Waga produktu z opakowaniem jednostkowym	2

Zdjęcia

